

## HANCOR SUMP PUMP WELL SPECIFICATION

### Scope

This specification describes Hancor's sump pump well for use in residential drainage applications.

### Requirements

The sump pump well shall be available in both 14-gallon (53 liter) and 19-gallon (72 liter) sizes. Each well shall have three pre-formed inlet collars sized to fit 4-inch (100mm) corrugated polyethylene drainage lines. Each well shall have a molded side panel designed to accept the outside basement perimeter line at any elevation along the well wall. Both wells shall have a twist-locking lid.

### Material Properties

Sump pump well material shall be high density polyethylene.

### Installation

Installation shall be in accordance with Hancor installation instructions and those issued by regional, state, or local agencies.

	A	B	C	D	E	F	G	H	I	J
14-gallon in.	12"	8"	14 1/4"	4 3/4"	20 3/8"	18 1/8"	24"	20 7/8"	18 3/8"	20 1/2"
53 liters (mm)	305mm	203mm	362mm	121mm	518mm	460mm	610mm	530mm	467mm	521mm
19-gallon in.	12	13	14 1/4	4 3/4	20 3/8	24	31 3/4	20 7/8	18 3/8	20 1/2
72 liters (mm)	(305)	(330)	(362)	(121)	(518)	(610)	(806)	(530)	(467)	(521)

