POLYGUARD 650 MASTIC

DESCRIPTION:

POLYGUARD 650 MASTIC is an asphalt/rubber based mastic which provides excellent adhesion to the **POLYGUARD 650 WATERPROOFING MEMBRANE**, structural concrete, masonry, and wood surfaces.

650 MASTIC is an integral part of the **POLYGUARD WATERPROOFING SYSTEM** and substitutions are not allowed.

USES:

650 MASTIC is designed to protect the termination edges, overlaps, patches, and any additional detailing areas. On vertical applications, **650 MASTIC** must be applied on both the bottom and top terminations of the **POLYGUARD WATERPROOFING SYSTEM**. **650 MASTIC** should not be applied where it will be immediately covered by **650 WATERPROOFING MEMBRANE**.

TECHNICAL DATA:

PHYSICAL PROPERTIES	TYPICAL RESULTS
Color	Black
Specific Gravity	1.12
Flash Point (PM Closed Cup)	105°F <i>(41°C)</i>

APPLICATION:

POLYGUARD 650 MASTIC is supplied either in a 5 gallon pail or in a 30 oz. caulking tube. If some material is applied with a caulking gun the bead must be struck with a trowel to insure the **650 MASTIC** is worked into the termination edges. If the material is supplied in a pail, it may be applied with either a trowel or by hand using rubber gloves as precautions. When applied as a temporary cut-off trowel the **650 MASTIC** over the membrane in a very thin layer, and allow to cure a minimum of 12 hours before placement of additional **650 WATERPROOFING MEMBRANE**.

On the bottom edge of any vertical application, *650 MASTIC* must be applied liberally to these areas. *650 MASTIC* should also be applied around any protrusions, drains, or any areas requiring patching, or specific detailing.

SAFETY, STORAGE, AND HANDLING INFORMATION:

POLYGUARD 650 MASTIC vapors are combustible. Refer to product label for handling precautions.



This Information is based on our best knowledge, but POLYGUARD cannot guarantee the results to be obtained.



MATERIAL SAFETY DATA:

All Material Safety Data Sheets and precautionary labels should be read and understood by all user supervisory personnel and employees before using. Consult **POLYGUARD PRODUCTS**, **INC.**'s Material Safety Data Sheets and OSHA regulations for additional safety and health information for the products described herein. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use of the product including waste disposal.

This is not a Material Safety Data Sheet and is not to be used as such. **POLYGUARD** has prepared separate Material Safety Data Sheets on each product.

TECHNICAL SERVICE AND AVAILABILITY:

Technical assistance, information and **POLYGUARD** products are available through a nationwide network of distributors and architectural representatives or contact **POLYGUARD PRODUCTS**, **INC**.

LIMITED WARRANTY:

POLYGUARD PRODUCTS, INC. has no control over the storage, handling or use of this product, thus the guarantee is limited to the purchase price of the defective material only.

This product is not covered by Polyguard Products ISO 9001 Quality System.

x: lit/arch/data sheets/30-650 Mastic.doc R1-22-08