

THE CAST IRON SUMP PUMP



Available from:

GORDON
ENERGY & DRAINAGE

913-764-6229 • gordonenergy.com

Features

- Cast Iron Sump/Effluent pump
- Energy efficient permanent split capacitor (PSC) motor
- Includes built-in vertical switch
- Cast iron vortex impeller
- Upper and lower ball bearings
- Carbon ceramic plus Buna N shaft seals
- Thermally protected
- Stainless steel fasteners
- Pumps solids up to 1/2"
- Removable strainer
- 10' Power cord (20' Option available)
- 3 Year limited warranty

Specifications

Model No.	CIS-33V	CIS-50V
Motor HP	1/3 HP	1/2 HP
GPM @ 10 ft	53	64
GPH @ 10 ft	3,200	3,840
Discharge	1.5" / 3.8 cm	1.5" / 3.8 cm
Amps @ 10'	5	5.5
Weight	21.1 lbs / 9.6 kg	22.1 lbs / 10.0 kg
Width	9" / 22.9 cm	9" / 22.9 cm
Depth	6.5" / 16.5 cm	6.5" / 16.5 cm
Height	11.75" / 29.8 cm	11.75" / 29.8 cm
Activation Level	7.125" / 18.1 cm	7.125" / 18.1 cm
Deactivation Level	2.25" / 5.7 cm	2.25" / 5.7 cm

Flow Chart

