



Ultra-Shield 1730 Waterproofing

Ultra-Shield 1730 Waterproofing is a polymer modified asphalt emulsion waterproofing membrane bridges shrinkage cracks and maintains its superior performance properties when exposed to the chemicals found in soil. Ultra-Shield 1730 complies with EPA Model Standard for radon control in new home construction. It may help contribute to LEED® credits.



Technical Data	
Solids	64% +/- 5% by weight
Application	Brush, roller, spray
Application Rate	22.5 ft.2/gal. (0.56 m2/L)
Elongation (ASTM D 412)	1850% min.
Weight	8.5 lbs. per gallon (1.02 gal./cu. cm.)
Flash point	n/a
Viscosity @ 77oF (25oC)	200 grams
Drying time @ 77oF (25oC)	4 hours to touch
Shelf life	1 year

Ultra-Shield is a trademark of GMX, Inc.

LEED Buildings and Leadership in Energy and Environmental Design are trademarks of the U.S. Green Building Council. The Leadership in Energy and Environmental Design (LEED) Green Building Rating System is a voluntary, consensus-building national standard that was initiated by the U.S. Green Building Council (USGBC) for developing high-performance sustainable solutions.



3800 E. 91st Street • Cleveland, OH 44105 • (866) 228-7743 • www.gmxwaterproofing.com

© 2016 Garland Industries, Inc.